

Fusibile cilindrico 10 A (31209)



Descrizione

Articolo

Cod.art.: 31209

Fusibile cilindrico 10 A

690 V, gR

10 x 38

Montaggio

Come accessorio

Gruppo di prodotti 17

Sottogruppo merceologico 83

Pz / conf. 10

EAN 4021267312091

Catalog page 2018 : 7.8

eCl@ss 6.1 27142002
27142002
ETIM 4.0 EC002704
ETIM 5.0 EC002704

Certificazioni

Norme

IEC 60269-1:2006 + A1:2009 + A2:2014
IEC 60269-2:2013
IEC 60269-4:2009 + A1:2012
IEC 60269-6:2010

Omologazioni

IEC (CB), UL



UL file: E180276, UL category (for USA): JFHR2 <http://www.ul.com>

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 10 A
Tensione nominale (IEC) AC: 690
V

Rated voltage (UL) AC: 700
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 1.3 W.
(The power dissipation for operation with rated current would be 2.1 W.)

Potere di interruzione AC: 200 kA

Valori meccanici

L x B x D: 38 x 10 x 10
Peso: 0.6 kg/100