

Sezionatore per fusibili, montaggio su barre (31232)



Descrizione

Articolo

Cod.art.: 31232

SECUR® 60Classic

Sezionatore per fusibili, montaggio su barre

per fusibili 10x38

3P

per barre 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 01

Sottogruppo merceologico 42

Pz / conf. 1

EAN 4021267312329

Catalog page 2018 : 3.18, 3.20

eCl@ss 6.1 27142190
27142190
ETIM 4.0 EC002705
ETIM 5.0 EC002705

Certificazioni

Norme

IEC 60947-1:2007 + A1:2010 + A2:2014

IEC 60947-3:2008 + A1:2012 + A2:2015

Type No.: SPL-10x38

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 32 A

Tensione nominale (IEC) AC: 690
V

Tensione nominale (IEC) DC: 110
V

Categoria d'impiego AC: AC-23A (400 V)
AC-22A (690 V)

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 3.4 W.

(The power dissipation for operation with rated current would be 5.3 W.)

Tensione di picco Uimp: 6 kV

Tensione max. IEC AC: 800
V

Tensione max. IEC DC: 110
V

cond. rated short-circuit current with fuses: 50 kA / 400 V AC (32A)

approved with fuse links of characteristics: gG

for fuse links gG and aM as per IEC / EN 60269-2

The function of isolation between incoming and outgoing contacts is provided by the opening of the switching mechanism as required in the standard.

Valori meccanici

L x H x P: 27 x 220 x 104

Peso: 76 kg/100

Poli: 3 poli

per barre: 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Type of fastening: patented click mechanism Tightening torque of box terminals 3 Nm

Proprietà materiali

Involucro: resistenza alle temperature fino a 140°C,
ignifugo secondo UL 94,

tenuta alle correnti di fuga CTI 225,

Senza silicio, senza alogeni

Levetta di temperatura stability 125°C,

manovra: self-extinguishing in acc. to UL 94,

creepage resistance CTI 200

Portafusibile: temperature stability 150°C,

self-extinguishing in acc. to UL 94,

creepage resistance CTI 125,

halogen-free

Copertura: temperature stability 125°C,

☐ fire behaviour UL 94 HB,


☐ creepage resistance CTI 200,

☐ halogen-free

Viti di screw +/- (PZ2), galvanized, chromized

collegamento:

Accessori




31901

Modulo laterale 9 mm



31902

Adattatore calibro D02 per fusibili D01 da 2 -16 A



31903

Microinterruttore di segnalazione

1 contatto di commutaz. 250 V AC / 5 A, 30 V DC / 4 A