

Base per fusibili D0, 27mm, montaggio su barre (31935)



Descrizione

Articolo

Cod.art.: 31935

CUSTO® 60Classic

Base per fusibili D0, 27mm, montaggio su barre

E 18 / 63 A

touch protected

per barre 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 01

Sottogruppo merceologico 03

Pz / conf. 8

EAN 4021267319359

Catalog page 2018 : 3.18

eCl@ss 6.1 27142120
27142120
ETIM 4.0 EC001644
ETIM 5.0 EC001644

Certificazioni

Norme

IEC 60269-1:2006 + A1:2009 + A2:2014

IEC 60269-3:2010 + A1:2013

Omologazioni

Germanischer Lloyd , VDE



Type No.: CEL18

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 63 A

Tensione nominale (IEC) AC: 400
V

Tensione nominale (IEC) DC: 250
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 3.8 W.

(The power dissipation for operation with rated current would be 5.9 W.)

Tensione di picco Uimp: 6 kV

Tensione max. IEC AC: 500
V

Tensione max. IEC DC: 250
V

cond. rated short-circuit current with fuses: 50 kA / 400 V AC

approved with fuse links of characteristics: gG

Direct contact of the fuse links on the busbar

for fuse links and gauge rings as per DIN VDE 0636-3 IEC / EN 60269-3

Valori meccanici

L x H x P: 27 x 200 x 35

Peso: 14.4 kg/100

Poli: 3 poli

per barre: 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Type of fastening: Click mechanism protects against movement Contact pressure provided by screw cap
E18 Tightening torque of box terminals 4Nm

Connessioni

morsetti a gabbia :

1,5 - 25 mm² cavi flessibili, direttam. o con ferrula,

1,5 - 10 mm² cavi rotondi

C. serr. 3,0 Nm

(cavi flessibili con ferrula potrebbero non più entrare, se scelti con sezione max.)

Proprietà materiali

Corpo base: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free

Viti di collegamento: screw +/- (PZ2), galvanized, chromized

Copertura: resistenza alle temperature fino a 125°C,
ignifugo secondo UL 94,
tenuta alle correnti di fuga CTI 600

Avvisi e consigli

D02 bus-mounting fuse bases are also suitable for D01 bus-mounting fuse bases thanks to special holding springs and special ferrule gauge pieces. From a permanent load of 35A, the 36mm-wide version is recommended due to the heat produced.

Accessori




01104

Tappo D02, porcellana

400 V

E 18



01729

Molla di ritenuta speciale per D01 in E18

2 - 16 A



31006

Tappo D02, plastica

400 V

E 18



31104

Tappo D02, plastica, con riduttore per fusibili D01

400 V, con foro per test

E 18



31904

Blocco tappo D02, versione utility tedesche

400 V

E 18




31910

Blocco tappo D02, versione industry

400 V

E 18

**79663**

Protezione laterale contro il contatto accidentale
agganciabile lateralmente
per strisce di copertura per basi D/D0