

Adattatore 250 A speciale, 3p (32023)



Descrizione

Articolo

Cod.art.: 32023

EQUES® 60Classic

Adattatore 250 A speciale, 3p

per ABB T-max XT4, Allen-Bradley 140G-J

105 x 190, collegamento al sistema in alto/basso

per barre 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 05

Sottogruppo merceologico 36

Pz / conf. 1

EAN 4021267320232

Catalog page 2018 : 3.14

eCl@ss 6.1 27370304
27370304
ETIM 4.0 EC001531
ETIM 5.0 EC001531

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

UL , Germanischer Lloyd



for UL feeder circuits >250V

Type No.: 60250.1-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 250 A

Tensione nominale (IEC) AC: 690 V

Rated current (UL): 250 A

Rated voltage (UL) AC: 600 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 26.1 W.

(The power dissipation for operation with rated current would be 40.8 W.)

rated isolation voltage U_i : 800

V

Tensione di picco U_{imp} : 6 kV

Tensione max. IEC AC: 800

V

Tensione max. IEC DC: 800

V

short-circuit
withstandability: the short-circuit capacity of the combination of adapter and MCCB
depends on the MCCB

SCCR: 25kA @ circuit breaker DIVQ/7 250A, 600Vac

65kA @ circuit breaker DIVQ/7 250A, 480Vac

Valori meccanici

L x H x P: 105 x 190 x 35

Peso: 122 kg/100

Poli: 3 poli

per barre: 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Proprietà materiali

Involucro: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free