

## Adattatore 250 A, speciale, 3p (32140)



### Descrizione

#### Articolo

Cod.art.: 32140

EQUES® 60Classic

Adattatore 250 A, speciale, 3p

per Eaton NZM2-XKR40 e NZM2-XKR4U

105 x 190, collegamento al sistema in alto/basso

per barre 12, 15, 20, 25, 30 x 5, 10 e barre profilate

#### Montaggio

60Classic

Gruppo di prodotti 05

Sottogruppo merceologico 36

Pz / conf. 1

EAN 4021267321406

Catalog page 2018 : 3.14

eCl@ss 6.1 27370304  
27370304  
ETIM 4.0 EC001531  
ETIM 5.0 EC001531

## Certificazioni

### Norme

IEC 61439-1:2011

### Omologazioni

CSA , UL , Germanischer Lloyd



for UL feeder circuits >250V

Type No.: 60250.1-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <http://directories.csa-international.org>

Omologazione CCC : no certification required

## Dati prodotto

### Valori elettrici

Corrente nominale (IEC): 250 A

Tensione nominale (IEC) AC: 690 V

Rated current (UL): 250 A

Rated voltage (UL) AC: 600 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 10 W.

(The power dissipation for operation with rated current would be 15.6 W.)

rated isolation voltage  $U_i$ : 800

V

Tensione di picco  $U_{imp}$ : 6 kV

Tensione max. IEC AC: 800

V

Tensione max. IEC DC: 800

V

let-through current  $I_d$ : 21,7 kA @ NZMH2 50kA / 600V

22,2 kA @ NZMH2 65kA / 480V

short-circuit withstandability: the short-circuit capacity of the combination of adapter and MCCB depends on the MCCB

SCCR: 50kA @NZMH2 600V

65kA @NZMH2 480V

### Valori meccanici

L x H x P: 105 x 190 x 35

Peso: 90.1 kg/100

Poli: 3 poli

per barre: 12, 15, 20, 25, 30 x 5, 10 e barre profilate

### Proprietà materiali

Involucro: temperature stability 125°C,  
self-extinguishing in acc. to UL 94,  
creepage resistance CTI 600,  
halogen-free