

Modulo N per adattatori EEC (32146)



Descrizione

Articolo

Cod.art.: 32146

Modulo N per adattatori EEC
per innesto ad entrambi lati

18 x 242

per barre 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 05

Sottogruppo merceologico 43

Pz / conf. 4

EAN 4021267321468

Catalog page 2018 : 3.12

eCl@ss 6.1 27370304
27370304
ETIM 4.0 EC001531
ETIM 5.0 EC001531

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

UL



Type No.: 680.1

UL file: E123577, UL category (for USA): NMTR2 <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR8 <http://www.ul.com>

Dati prodotto

Valori elettrici

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0.9 W.

(The power dissipation for operation with rated current would be 1.4 W.)

Connecting terminals 16 mm² top and bottom

Valori meccanici

L x H x P: 18 x 242 x 50

Peso: 14.1 kg/100

per barre: 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Torque for busbar contacting 12Nm

Torque for pipe connection 40Nm

Avvisi e consigli

For feeding and tapping the PE/N busbar

version is without connection leads

assembly on the 60mm-System only possible in conjunction with an adapter or device carrier

both sides can be plugged onto all adapters, device carriers and side-mounted modules.