


Adattatore EEC 63 A (32591)



Descrizione

Articolo

Cod.art.: 32591

EQUES® 30Compact

Adattatore EEC 63 A

con 1 guida DIN scorrevole

54 x 160, con cavi AWG 8 (10 mm²)

per barre 12 x 5, 10

Montaggio

30Compact 3P

Gruppo di prodotti 05

Sottogruppo merceologico 24

Pz / conf. 4

EAN 4021267325916

Vantaggi prodotto

Conductor ends ultrasonically sealed.

Click mechanism when pushing onto the busbar.

Catalog page 2018 : 2.3

eCl@ss 6.1 27370304

27370304

ETIM 4.0 EC001531

ETIM 5.0 EC001531

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

UL , Germanischer Lloyd



for UL feeder circuits >250V

Type No.: EEC6063C-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 63 A

Tensione nominale (IEC) AC: 690
V

Rated current (UL): 65 A

Rated voltage (UL) AC: 600
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 4.4 W.

(The power dissipation for operation with rated current would be 6.9 W.)

rated isolation voltage U_i : 800

V

Tensione di picco U_{imp} : 6 kV

Tensione max. IEC AC: 800

V

Tensione max. IEC DC: 800

V

short-circuit
withstandability: the short-circuit capacity of the combination of adapter and motor starter
depends on the motor starter

Valori meccanici

L x H x P: 54 x 160 x 63

Peso: 21.8 kg/100

Poli: 3 poli

per barre: 12 x 5, 10

Proprietà materiali

Involucro: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free

Guida: temperature stability 125°C,
DIN: self-extinguishing in acc. to UL 94,
creepage resistance CTI 550,
halogen-free

Viti: screw +/- (PZ1), galvanized, chromized

Conductor insulation: temperature-resistant up to 105 °C

Avvisi e consigli

For compact mounting of complete motor circuits with commercially available switchgear and safe mechanical and electrical connection to the busbar system.

Accessori



32912

Modulo laterale per adattatori EEC, innestabile ad entrambi i lati
per 32590 e 32591

9 x 160