

Adattatore EPC 630 A speciale, 3p (32978)



Descrizione

Articolo

Cod.art.: 32978

EQUES® 60Classic

Adattatore EPC 630 A speciale, 3p

per Eaton NZM3-XKR13O, NZM3-XKR13U

140 x 300, coll.al sistema in alto / basso

per barre 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 05

Sottogruppo merceologico 42

Pz / conf. 1

EAN 4021267329785

Catalog page 2018 : 3.15

eCl@ss 6.1 27370304
27370304
ETIM 4.0 EC001531
ETIM 5.0 EC001531

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

UL , Germanischer Lloyd



for UL feeder circuits >250V

Type No.: EPC60630-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 630 A

Tensione nominale (IEC) AC: 690 V

Rated current (UL): 630 A

Rated voltage (UL) AC: 600 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 61.8 W.

(The power dissipation for operation with rated current would be 96.6 W.)

rated isolation voltage U_i : 800

V

Tensione di picco U_{imp} : 6 kV

Tensione max. IEC AC: 800

V

Tensione max. IEC DC: 800

V

short-circuit
withstandability: the short-circuit capacity of the combination of adapter and MCCB
depends on the MCCB

SCCR: 30 kA

Valori meccanici

L x H x P: 140 x 300 x 35

Peso: 250 kg/100

Poli: 3 poli

per barre: 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Proprietà materiali

Involucro: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free