


Adattatore 580 A speciale, 3p (32980)



Descrizione

Articolo

Cod.art.: 32980

EQUES® 60Classic

Adattatore 580 A speciale, 3p

per Siemens 3VL5

184 x325, coll.al sistema in alto

per barre 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 05

Sottogruppo merceologico 42

Pz / conf. 1

EAN 4021267329808

Catalog page 2018 : 3.15

eCl@ss 6.1 27370304
27370304
ETIM 4.0 EC001531
ETIM 5.0 EC001531

Certificazioni

Norme

IEC 61439-1:2011

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 580 A

Tensione nominale (IEC) AC: 690 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 53.4 W.

(The power dissipation for operation with rated current would be 83.4 W.)

rated isolation voltage U_i : 800
V

Tensione di picco U_{imp} : 6 kV

Tensione max. IEC AC: 800
V

Tensione max. IEC DC: 800
V

short-circuit
withstandbility: the short-circuit capacity of the combination of adapter and MCCB
depends on the MCCB

Valori meccanici

L x H x P: 184 x 325 x 88

Peso: 276 kg/100

Poli: 3 poli

per barre: 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Proprietà materiali

Involucro: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free