


Adattatore EEC 100 A speciale, 3p (32981)



Descrizione

Articolo

Cod.art.: 32981

EQUES® 60Classic

Adattatore EEC 100 A speciale, 3p

per ABB MS49X e Siemens 3RV, grand. S3, lungh. 200 mm

72 x 200, con cavi AWG 4 (25 mm²), con piastra metallica, coll.al sistema in alto
per barre 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 05

Sottogruppo merceologico 27

Pz / conf. 1

EAN 4021267329815

Vantaggi prodotto

Conductor ends ultrasonically sealed.

Click mechanism when pushing onto the busbar.

Catalog page 2018 : 3.13

eCl@ss 6.1 27370304

27370304

ETIM 4.0 EC001531

ETIM 5.0 EC001531

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

CSA , UL



for UL feeder circuits >250V

Type No.: EEC60100-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <http://directories.csa-international.org>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 100 A

Tensione nominale (IEC) AC: 690 V

Rated current (UL): 100 A

Rated voltage (UL) AC: 600 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 4.6 W.

(The power dissipation for operation with rated current would be 7.3 W.)

rated isolation voltage U_i : 800

V

Tensione di picco U_{imp} : 6 kV

Tensione max. IEC AC: 800

V

Tensione max. IEC DC: 800

V

short-circuit the short-circuit capacity of the combination of adapter and MCCB

withstandbility: depends on the MCCB

SCCR: 65kA @ circuit breaker Siemens S3

Valori meccanici

L x H x P: 72 x 200 x 63

Peso: 66 kg/100

Poli: 3 poli

per barre: 12, 15, 20, 25, 30 x 5, 10 e barre profilate

Proprietà materiali

Involucro: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free