

Base per fusibili cilindr. Class J, connessione in basso / alto (33311)



Descrizione

Articolo

Cod.art.: 33311

QUADRON® 60Classic

Base per fusibili cilindr. Class J, connessione in basso /alto
per fusibili class J, 225 - 400 A (54 x 181)

3p, con morsetto a gabbia

per barre 12, 20, 30 x 10 e barre profilate

Montaggio

60Classic

Gruppo di prodotti 16

Sottogruppo merceologico 33

Pz / conf. 1

EAN 4021267333119

Vantaggi prodotto

the product is based on the UL approval in category IZLT2 also listed in category NMTR (file E123577)

Catalog page 2018 : 3.21

eCl@ss 6.1 27142190

27142190

ETIM 4.0 EC002705

ETIM 5.0 EC002705

Certificazioni

Norme

UL 4248-1 Ed. 1

UL 4248-8 Ed. 1

Omologazioni

CSA , UL



for UL feeder circuits >250V

Type No.: JC400B

UL file: E230163, UL category (for USA): IZLT2 <http://www.ul.com>

UL file 2: E123577, UL category+ (for USA): NMTR <http://www.ul.com>

UL file: E230163, UL category (for Canada): IZLT8 <http://www.ul.com>

UL file 2: E123577, UL category+ (for Canada): NMTR7 <http://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <http://directories.csa-international.org>

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 400 A

Tensione nominale (IEC) AC: 600 V

Tensione nominale (IEC) DC: 600 V

Rated current (UL): 400 A

Rated voltage (UL) AC: 600 V

Rated voltage (UL) DC: 600 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 30 W.

(The power dissipation for operation with rated current would be 46.8 W.)

Tensione max. IEC AC: 600

V

Tensione max. IEC DC: 600

V

SCCR: 65 kA

for Class J fuses 225 - 400A as per UL 248-8 (54x181)

Valori meccanici

L x H x P: 256 x 285 x 122

Peso: 690 kg/100

Poli: 3 poli

per barre: 12, 20, 30 x 10 e barre profilate

Conessioni

tunnel terminal with hole of 23,0 mm diameter

acc. to IEC / EN :

16 - 240 (300) mm²

flexible cables, directly or with wire-end ferrule,

solid and stranded round cables,

Md 38 - 40 Nm

(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

acc. to UL :

AWG 4 - MCM 600

stranded cables Class B acc. to UL 486E

336 - 355 lb.in.

Proprietà materiali

Corpo base:	temperature stability 125°C, self-extinguishing in acc. to UL 94, creepage resistance CTI 200, halogen-free
Protezione contro contatto accidentale:	temperature stability 125°C, ☐ fire behaviour UL 94 HB, ☐ creepage resistance CTI 200, ☐ halogen-free
Viti di collegamento:	screw M12, galvanized, chromized

Avvisi e consigli

Shock protection through push-on covers.

Altre versioni

Version for mounting plate: Part no. 33308

Accessori



03224

Fusibile 250 A, (fast acting) rapido
600 V AC
Class J, 54 x 181



03225

Fusibile 300 A, (fast acting) rapido
600 V AC
Class J, 54 x 181



03226

Fusibile 350 A, (fast acting) rapido
600 V AC
Class J, 54 x 181



03227

Fusibile 400 A, (fast acting) rapido
600 V AC
Class J, 54 x 181



03238

Fusibile 250 A, (time delay) ritardato
600 V AC, 300 V DC
Class J, 54 x 181



03239

Fusibile 300 A, (time delay) ritardato
600 V AC, 300 V DC
Class J, 54 x 181

**03240**

Fusibile 350 A, (time delay) ritardato

600 V AC, 300 V DC

Class J, 54 x 181

**03241**

Fusibile 400 A, (time delay) ritardato

600 V AC, 300 V DC

Class J, 54 x 181