

Base per fusibili cilindr. (33409)



Descrizione

Articolo

Cod.art.: 33409

QUADRON® Panel

Base per fusibili cilindr.

class J / 3p, morsetti 150 mm²

200 A / 600 V (41 x 146)

Montaggio

Pannello / piastra di fondo

Gruppo di prodotti 16

Sottogruppo merceologico 12

Pz / conf. 1

EAN 4021267334093

Catalog page 2018 : 6.10

eCl@ss 6.1 27142190
27142190
ETIM 4.0 EC002705
ETIM 5.0 EC002705

Certificazioni

Norme

UL 4248-1 Ed. 1

UL 4248-8 Ed. 1

Omologazioni

UL



for UL feeder circuits >250V

Type No.: QCC-ClassJ200A

UL file: E230163, UL category (for USA): IZLT2 <http://www.ul.com>

UL file: E230163, UL category (for Canada): IZLT8 <http://www.ul.com>

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 200 A

Tensione nominale (IEC) AC: 600 V

Tensione nominale (IEC) DC: 600 V

Rated current (UL): 200 A

Rated voltage (UL) AC: 600 V

Rated voltage (UL) DC: 600 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 8.3 W.

(The power dissipation for operation with rated current would be 13 W.)

Tensione max. IEC AC: 600
V
Tensione max. IEC DC: 600
V

SCCR: 200 kA

Special operating conditions corresponding to IEC / EN 61439-1 may yield to faulty activations of pilot switches and fuse monitors. The operating conditions have to be considered for the analysis of status signals.

for Class J fuses 110 - 200A as per UL 248-8 (41x146)

Valori meccanici

L x H x P: 184 x 263 x 112
Peso: 203 kg/100
Poli: 3 poli

Conessioni

AWG 2 - MCM 300 stranded, equivalent to 33,6 - 152mm²


Proprietà materiali

Corpo: temperature stability 125°C,
base: self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free
Coperchio: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200,
halogen-free

Altre versioni

Version for 60mm-System: Part no. 33403

Accessori



33142

Copertura per capicorda, innestabile in alto / basso

per QCB / QCS-NH 1, QCS 320A

QCB-NH1, QCS-NH1, QCS 320 A