

Adattatore 16 A, con tecnologia CrossLink® (36009)



Descrizione

Articolo

Cod.art.: 36009

EQUES® CrossBoard Slim

Adattatore 16 A, con tecnologia CrossLink®

1 guida DIN fissa, con vano per fusibili 10x38 / class CC

22,5 x 160, con cavi AWG 14 (2,5mm²)

Montaggio

CrossBoard®

Gruppo di prodotti 05

Sottogruppo merceologico 21

Pz / conf. 1

EAN 4021267360092

Vantaggi prodotto

Leitungsenden ultraschallverdichtet.

Catalog page 2018 : 1.3

eCl@ss 6.1 27370304
27370304

ETIM 4.0 EC001531

ETIM 5.0 EC001531

Certificazioni

Norme

IEC 61439-1:2011

Omologazioni

IEC (CB) , UL



for UL feeder circuits >250V

Type No.: EQ22-A1

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

Omologazione CCC : no certification required

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 16 A

Tensione nominale (IEC) AC: 690
V

Rated current (UL): 12.5 A

Rated voltage (UL) AC: 600 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 2.6 W.

(The power dissipation for operation with rated current would be 4 W.)

Tensione di picco Uimp: 6 kV

SCCR: 50kA@Class CC 20A / 600VAC

Valori meccanici

L x H x P: 22.5 x 160 x 85

Peso: 12.9 kg/100

Poli: 3 poli

Proprietà materiali

Involucro: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free

Avvisi e consigli

Cylindric fuses are not included

You find [here](#) recommended fuses