

Avviatore ibrido (36110)



Descrizione

Articolo

Cod.art.: 36110

MOTUS® CrossBoard

Avviatore ibrido

modulo elettronico 0,18 - 2,4 A, per avviamento diretto o con inversione di marcia
con tecnologia CrossLink®

Montaggio

CrossBoard®

Come accessorio

Gruppo di prodotti 21

Sottogruppo merceologico 51

Pz / conf. 1

EAN 4021267361105

Catalog page 2018 : 1.2, 2.3, 3.16, 6.1

eCl@ss 6.1 27370804
27370804
ETIM 4.0 EC001037
ETIM 5.0 EC001037

Certificazioni

Norme

EN 60947-1:2015
EN 60947-4-2:2013
EN 61439-1:2012
EN 50495:2010

Omologazioni

UL



for UL feeder circuits >250V

Type No.: 36110

UL file: E360470, UL category (for USA): NLDX <http://www.ul.com>

UL file: E360470, UL category (for Canada): NLDX7 <http://www.ul.com>

Dati prodotto

Valori elettrici

Corrente nominale (IEC): 2.4 A

Tensione nominale (IEC) AC: 500
V

Rated voltage (UL) AC: 500
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 3.5 W.

(The power dissipation for operation with rated current would be 5.5 W.)

rated isolation voltage U_i : 500
V
Tensione di picco U_{imp} : 6 kV
Tensione max. IEC AC: 500
V

short-circuit withstandability: determined by main product

Valori meccanici

L x H x P: 22,5 x 160 x 119,5
Peso: 50.9 kg/100
Poli: 3 poli

Proprietà materiali

Involucro: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free