

## Avviatore ibrido (36111)



### Descrizione

#### Articolo

Cod.art.: 36111

MOTUS® CrossBoard

Avviatore ibrido

modulo elettronico 1,5 - 9 A, per avviamento diretto o con inversione di marcia  
con tecnologia CrossLink®

#### Montaggio

CrossBoard®

Come accessorio

Gruppo di prodotti 21

Sottogruppo merceologico 51

Pz / conf. 1

EAN 4021267361112

Catalog page 2018 : 1.2, 2.3, 3.16, 6.1

eCl@ss 6.1 27370804  
27370804  
ETIM 4.0 EC001037  
ETIM 5.0 EC001037

## Certificazioni

### Norme

EN 60947-1:2015  
EN 60947-4-2:2013  
EN 61439-1:2012  
EN 50495:2010

### Omologazioni

UL



for UL feeder circuits >250V

Type No.: 36111

UL file: E360470, UL category (for USA): NLDX <http://www.ul.com>

UL file: E360470, UL category (for Canada): NLDX7 <http://www.ul.com>

## Dati prodotto

### Valori elettrici

Corrente nominale (IEC): 9 A  
Tensione nominale (IEC) AC: 500  
V

Rated voltage (UL) AC: 500  
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 7.7 W.

(The power dissipation for operation with rated current would be 12 W.)

rated isolation voltage U<sub>i</sub>: 500  
V  
Tensione di picco U<sub>imp</sub>: 6 kV  
Tensione max. IEC AC: 500  
V

short-circuit withstandbilty: determined by main product

### **Valori meccanici**

L x H x P: 22,5 x 160 x 119,5  
Peso: 50.9 kg/100  
Poli: 3 poli

### **Proprietà materiali**

Involucro: temperature stability 125°C,  
self-extinguishing in acc. to UL 94,  
creepage resistance CTI 600,  
halogen-free