


## Curva Discesa a 45° con Coperchio



T0 099 0510

Lunghezza: 0

## Finiture

- |    |                                                    |
|----|----------------------------------------------------|
| 01 | Zincato Sendzimir - UNI EN 10346                   |
| 03 | Zincatura a caldo per immersione - UNI EN ISO 1461 |
| 11 | Grigio RAL 7032 - ISO9227-ISO6270-ISO2810          |
| 15 | Blu RAL 5015 - ISO9227-ISO6270-ISO2810             |
| 40 | Inox AISI 304 - UNI EN 10088                       |
| 41 | Inox AISI 316L - UNI EN 10088                      |

| Caratteristiche Tecniche |      |
|--------------------------|------|
| Dimensione               |      |
| B                        | 100  |
| Peso                     |      |
| [Kg]                     | 0,40 |
| Dati Tecnici             |      |
| a                        | 101  |
| b                        | 157  |
| R                        | 100  |

## Sistema Certificato

- IMQ
  - EN 61537-1 ed.2007
  - EN 50085-1:2005 ed EN 50085-2-1:2006
  - UL file E471266
- Attenzione: per materiale Serie ZT e ZM  
venduto/installato in USA e Canada, richiedere la  
marcatura UL

**Spessori**

T1 099 - Componente - 1,00mm

T1 100 - Coperchio - 0,80mm

**\*T0 099 0507 - Misura a richiesta**

## Certificazioni

