


## Curva Discesa a 30° con Coperchio



T0 101 1020

Lunghezza: 0

Finiture

- 01 Zincato Sendzimir - UNI EN 10346
- 03 Zincatura a caldo per immersione - UNI EN ISO 1461
- 11 Grigio RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blu RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Inox AISI 304 - UNI EN 10088
- 41 Inox AISI 316L - UNI EN 10088

### Caratteristiche Tecniche

| Dimensione   |      |
|--------------|------|
| B            | 200  |
| Peso         |      |
| [Kg]         | 0,65 |
| Dati Tecnici |      |
| a            | 130  |
| b            | 156  |
| R            | 100  |

### Sistema Certificato

- IMQ
  - EN 61537-1 ed.2007
  - EN 50085-1:2005 ed EN 50085-2-1:2006
  - UL file E471266
- Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL

### Spessori

T1 101 - Componente - 1,00mm

T1 102 - Coperchio - 0,80mm

**\*T0 101 0507 - Misura a richiesta**

### Certificazioni



E471266

