


## Flangia per attacco a quadro



TO 260 0750

Lunghezza: 0

Finiture

- 01 Zincato Sendzimir - UNI EN 10346
- 03 Zincatura a caldo per immersione - UNI EN ISO 1461
- 11 Grigio RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blu RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Inox AISI 304 - UNI EN 10088

### Caratteristiche Tecniche

| Dimensione   |      |
|--------------|------|
| B            | 500  |
| Spessore     |      |
| [mm]         | 1,50 |
| Peso         |      |
| [Kg]         | 0,48 |
| Dati Tecnici |      |
| a            | 125  |
| b            | 550  |
| c            | 525  |
| d            | 100  |

### Sistema Certificato

- IMQ
  - EN 61537-1 ed.2007
  - EN 50085-1:2005 ed EN 50085-2-1:2006
  - UL file E471266
- Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL

### Certificazioni



## Flangia per attacco a quadro

### Montaggio

H 50  n. 2 M6x10 / M6x12 **TO 620 0610 / TO 620 0612**

 n. 2 M6 **TO 621 0600**

per ogni flangia

H 75-100  n. 4 M6x10 / M6x12 **TO 620 0610 / TO 620 0612**

 n. 4 M6 **TO 621 0600**

per ogni flangia

*Non compresi*

