


Flangia per attacco a quadro



TO 260 1060

Lunghezza: 0

Finiture

- 01 Zincato Sendzimir - UNI EN 10346
- 03 Zincatura a caldo per immersione - UNI EN ISO 1461
- 11 Grigio RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blu RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Inox AISI 304 - UNI EN 10088

Caratteristiche Tecniche

Dimensione	
B	600
Spessore	
[mm]	1,50
Peso	
[Kg]	0,59
Dati Tecnici	
a	150
b	650
c	625
d	125

Sistema Certificato

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
- Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL

Certificazioni



Flangia per attacco a quadro

Montaggio

H 50  n. 2 M6x10 / M6x12 **TO 620 0610 / TO 620 0612**

 n. 2 M6 **TO 621 0600**

per ogni flangia

H 75-100  n. 4 M6x10 / M6x12 **TO 620 0610 / TO 620 0612**

 n. 4 M6 **TO 621 0600**

per ogni flangia

Non compresi

