

Data sheet

030M4T44

Manipolatore, 4 posizioni, 4 Temporanee, 4 N.O.+4 N.C.



Features

Range	030 Comando e Segnalazione EL-SG Ø 30
Product	Manipolatori Ø 30
Type	4 posizioni temporanee
Item code	030M4T44
Description	Manipolatore, 4 posizioni, 4 Temporanee, 4 N.O.+4 N.C.
Colour	Nero
Weight - gr	206,000
Custom tariff no.	85365080
GTIN	8052878029333

Technical data

Approvals	CE, (UL-CSA Microswitch only)
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	10.000.000 Operations
Cap or bellow material	Silicon rubber
Housing material	PA Polyamide
External bezel material	Chromed zinc alloy
Internal parts material	Lever and springs made in stainless steel AISI 304
Internal parts material	Sliding bushing made in brass
Microswitches flange material	Stainless steel AISI 304
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Rated insulation voltage	Ui 300V - Uimp 2.5KV (EN-IEC60947-1)
Overvoltage category	Class I (IEC-EN61140)
Microswitch contact form	SPDT (single pole double throw)
Microswitch terminals	Quick connect #250
Microswitch electrical ratings	250VAC - 16A (resistive load)
Microswitch electrical ratings	250VDC - 0.3A / 125VDC - 0.6A (resistive load)
Microswitch electrical durability	100.000 operations
Warranty period	18 months

Data sheet

030M4T44

Manipolatore, 4 posizioni, 4 Temporanee, 4 N.O.+4 N.C.

Technical drawings

