



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	2/0 AWG
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric
Wire Strip Length	1-1/16 in.
Stud Size	5/16 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BLACK
Panduit Die Index No. on Barrel	P45
Alternate Industry Die Index No. ( ) on Barrel	(13)
Plating Temperature Range	-40°C to 150°C



REV	DATE	BY	CHK	DESCRIPTION	ECN
02	2/22	JHNU	RUMO	ADDED PLATING TEMPERATURE RANGE TO TABLE	117540
01	5/04	DRL	DRL	ADDED UL, CSA AND PART NO. TO STAMP	11806

**PANDUIT CORP. TINLEY PARK, ILLINOIS**

LCA2/0-56F-X  
Copper Lug - One-Hole, Standard Barrel, 90° Angle Tongue

SCALE N/A DRAWING NO / CAD FILE LCA2\_0-56F-CUST