Plating Wire Size			Electro-Tin  6 AWG	-				
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	-	.20±.02 DIA(3) PLS		.31 R REF.  Color coded barrel markings	
Wire Strip Length		٦	1-1/8 in.	1		D S C		
Stud Size			#10	.46±.04	PANDUIT (#)	6 STR CU LCC6-10ABW	PANDUIL .13 REF.	
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.23±.04 -		.63±.02		
UL Temperature Rating			90°C			75±.02 —		
C.S.A Certified Wire Connector			Yes			., 02.02		
Panduit Color Code on Barrel		ode	BLUE		•	2.52±.06  Wire inspection window  Beveled wentry  2.22±.01 .31±		
Panduit Die Index No. on Barrel		ex No.	P24					
Alternate Industry Die Index No. ( ) on Barrel			(7)		Wire inspec			
	CF	ERTIFIED	D LISTED Wire Connector	.08±.01			1.22.01 .512.0	
							CORP. TINLEY PARK, ILLINO	
2 5/08 JHNU JHNU REVISED MARKING 1		O 3 BANDS			LCC6-10ABW-L Copper Lug - Slotted Two-Hole, Long Barrel with Window			
2   5/UK	EV DATE BY CHK		DESCRIPTION					