THIS	COPY IS I	PROVID	ED ON	A RESTRICTED BASIS AND IS NOT TO BE US	ED IN ANY WAY DETRIMENTAL	. то ті	IE INTE	ERESTS OF PANDUIT CORP.	
N	Naterial			High Conductivity Seamless Copper Tube					
P	lating			Electro-Tin					
W	Wire Size			3/0 AWG					
M	Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric		.45 R Ref Color coded barrel markings			
W	Wire Strip Length			1-3/16 in.					
St	Stud Size			3/8 in.	.96±.04				
	UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.39±.04	- 1	00±.0	0241±.02 DIA (2) PLS	
	UL Temperature Rating			90° C				3.33±.06	
	C.S.A Certified Wire Connector			Yes					
	Panduit Color Code on Barrel		ode	ORANGE					
	Panduit Die Index No. on Barrel		ex No.	P50	Wire insp	ectic	n win	dow 1.14±.04Beveled wire entry	
D	Alternate Industry Die Index No. () on Barrel			(14)	I			.51±.01 .64±.01	
		CE	ERTIFIEL	 B LISTED Wire Connector 	.13±.01				
								ANDUIT CORP. TINLEY PARK, ILLINOIS	
)1	7/12	ІНКІЦ	ЈНИЦ	REMOVED NAVY NUMBER	N10884TQ-LCD3/0-38D-CUST	RGB	RGB	LCD3/0-38D-X Copper Lug - Two-Hole, Standard Barrel	
51	DATE	11110	CHK	DESCRIPTION	11100041Q-LCD3/0-30D-C031	NOD	SIID		