

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

	NOMINAL DUCT SIZE (W X H)	A IN (mm)	D IN (mm)	E IN (mm)	F IN (mm)	K IN (mm)	W IN (mm)	H IN (mm)	H TOL ( <u>+</u> )	T IN (mm)	T TOL ( <u>+</u> )
	.5X.5	.63 (16.0)	.38 (9.7)	.37 (9.4)	.80 (20.3)		.51 (13.0)	.50 (12.7)	.06 (1.6)	.05	.02
	.5X1	77	.75 (19.1)	.31 (7.9)	***		.51 (13.0)	1.00 (25.4)	**	.06 (1.4)	77
	.75X.75	.88 (22.4)		**	.76 (19.3)	.75 (19.1)	vv	.05 (1.3)	**		
		77	.75 (19.1)	**	77		TT	1.00 (25.4)	vv	.06 (1.4)	VV
	.75X1.5		1.20 (30.5)	**	***		TT	1.50 (38.1)	**	.07 (1.7)	VV
	.75X2	77	1.63	**	**	Щ	***	2.00 (50.8)	**	.07 (1.8)	.02 (0.6)
. [	1×1	1.14	.75 (19.1)	ΨΨ	**	CENTERL I NE	1.02 (25.9)	1.00 (25.4)	vv	.06 (1.4)	.02 (0.4)
	1X1.5	77	1.20 (30.5)	**	77		TT	1.50 (38.1)	**	.07 (1.7)	77
	1 X 2	77	1.63	**	***		***	2.00 (50.8)	**	.07 (1.8)	.02
	1 X 3	**	2.63 (66.8)	**	1.00 (25.4)		***	3.00 (76.2)	.10 (2.5)	.07 (1.8)	**
	1×4	77	3.63 (92.2)	77	***		77	4.00 (101.6)	vv	.08	**
	1.5X1.5	1.64	1.20 (30.5)	.31 (7.9)	.80 (20.3)		1.52 (38.6)	1.50 (38.1)	.06 (1.6)	.07 (1.7)	.02
	1.5X2	**	1.63 (41.4)	**	**		***	2.00 (50.8)	vv	.07 (1.8)	.02
	1.5X3	77	2.63 (66.8)	**	1.00 (25.4)		77	3.00 (76.2)	.10 (2.5)	.07 (1.8)	VV
	1.5X4	**	3.63 (92.2)	**	77		***	4.00 (101.6)	77	.08 (1.9)	**

>= AVAILABLE AS "NS: SOLID WALL DUCT

							WIRING DUCT SPECIFICATIONS TYPES "NS", "NE"
							CUSTOMER DRAWING  ITEM REVISION NAME  D34175BI/05  DATASET FILE NAME  DATASET PLANTING DATASET PROPERTY.
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]
6	09-16-15	JBN	MRJS	RGRO	SEE SHEET 1 FOR REVSION DESCRIPTION	34175-08	.x ± .xxx ± .xx ± .xxx ± .xx ± .xxx ±
5 5	02-25-13	JBN	RTFI	RTFI	SEE SHEET 1 FOR REVSION DESCRIPTION	34175-08	THIRD ANGLE PROJECTION 34175-08
RE	V DATE	ВҮ	CHK	APR	DESCRIPTION	ECN	DRAWN BY DATE  DW 10-29-91 BKR NONE SHT 2 OF 3

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

	NOMINAL DUCT SIZE (W X H)	A IN (mm)	D IN (mm)	E IN (mm)	F IN (mm)	K IN (mm)	W IN (mm)	H IN (mm)	H TOL ( <u>±</u> )	T I N ( mm )	T TOL ( ± )
	2X1	2.14 (54.4)	.75 (19.1)	.31 (7.9)	.80 (20.3)	.50 (12.7)	2.02 (51.3)	1.00 (25.4)	.06 (1.6)	.06 (1.4)	.02
	2X1.5	**	1.20 (30.5)	77	***	77	**	1.50 (38.1)	ψΨ	.07 (1.6)	**
>	2X2	**	1.63 (41.4)	77	**	77	**	2.00 (50.8)	ΨΨ	.07 (1.8)	.02 (0.6)
	2X3	77	2.63 (66.8)	77	1.00	77	**	3.00 (76.2)	.10 (2.5)	.07 (1.8)	77
	2X4	77	3.63 (92.2)	44	**	77	**	4.00 (101.6)	ΨΨ	.08 (1.9)	97
	2.5X3	**	2.63 (66.8)	**	***	.75 (19.1)	2.52 (64.0)	3.00 (76.2)	VV	.07 (1.8)	**
	3X1	3.14 79.8)	.75 (19.1)	77	.80 (20.3)	1.00 (25.4)	3.02 (76.7)	1.00 (25.4)	.06 (1.6)	.06 (1.4)	.02 (0.4)
	3X1.25	77	1.00 (25.4)	77	**	77	***	1.25 (31.8)	V V	.06 (1.5)	77
	3X2	77	1.63	**	**	77	**	2.00 (50.8)	V V	.07 (1.8)	.02 (0.6)
>	3X3	77	2.63 (66.8)	**	1.00	77	**	3.00 (76.2)	.10 (2.5)	.07 (1.8)	77
	3X4	77	3.63 (92.2)	77	**	77	***	4.00 (101.6)	77	.08 (1.9)	77
	3X5	***	4.63 (117.6)	.38 (9.7)	1.33	77	***	5.00 (127.0)	**	.09 (2.3)	.03 (0.6)
	4X1.5	4.14 (105.2)	1.20 (30.5)	.31 (7.9)	.80 (20.3)	1.50 (38.1)	4.02 (102.1)	1.50 (38.1)	.06 (1.6)	.07 (1.6)	.02 (0.4)
	4X2	77	1.63	77	**	77	***	2.00 (50.8)	**	.07 (1.8)	.02 (0.6)
	4X3	77	2.63 (66.8)	77	1.00	77	***	3.00 (76.2)	.10 (2.5)	.07 (1.8)	77
> [	4X4	**	3.63 (92.2)	**	***	**	**	4.00 (101.6)	**	.08 (1.9)	**
	4X5	77	4.63 (117.6)	.38 (9.7)	1.33 (33.8)	77	**	5.00 (127.0)	**	.09 (2.3)	.03 (8.0)
	\ - Λ\/Λ II	<u> </u>	A C 88 N I			A / A					

>= AVAILABLE AS "NS: SOLID WALL DUCT

<b>.</b>							WIRING DUCT SPECIFICATIONS TYPES "NS", "NE"
							CUSTOMER DRAWING
							D34175BI/05  DATASET FILE NAME  DO447FPI D049F4
							D34175BI_DC705A
							UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]
6	09-16-15	JBN	MRJS	RGRO	SEE SHEET 1 FOR REVSION DESCRIPTION	34175-08	.xxx ± .xxx ± MODIFIED POLYPHENYLENE OXIDE
5	02-25-13	JBN	RTFI	RTFI	SEE SHEET 1 FOR REVSION DESCRIPTION	34175-08	THIRD ANGLE PROJECTION THIRD ANGLE 34175-08
RE\	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE  DW 10-29-91 BKR NONE SHT 3 0F 3